

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS REVISIONS								
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED			
1		RELEASED FOR PRODUCTION.	2/2/2017	RJC	JAG			





NOTE:

- 1. REF. AIRBUS T/N M632V6009124.
- 2. PART OF KIT RBEM632V6009102.

 $\sqrt{3}$ USE -9 TO BOND -3 TO -1.


TITLE

UNDOG CLUTCH BLANK

DWG NO. RBEM632V6009124


							- 1		
	MAT'L				UNLESS OTHERWISE SPECIFIED				
	HEAT				DIMENSIONS ARE IN INCHES				
	TREAT				.XXX ± .005 FRACTIONS ± 1/8				
	FINISH				.XX ± .01	ANGLES ±.5°	١		
	0050				.X ± .1	SURFACES = 125/	1		
	SPEC				1. BREAK ALL SHARP EDGES				
	DRAWN BY:	+		.015 x 45° OR .015R					
	CHECKED: DUERFELDT					IAL LIMITS APPLY	1		
	CHECKED:	DUERFE	LDI		AFTER PLATING				
	OPPS APPR:	ANDERS	INOS		3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009				
	ANDLINGON				ASME 114.5M-2009				
	QA APPR: LINDSAY				USED ON MODEL				
	APPROVED:	GILBERT			H175				
					11170				
;	SCALE	1:2	DATE	6/1	13/2016	SHEET 1 OF 3			


	ASSY QTY	ASSY QTY	B/O	Part #	# UNIT Description		Material	B/O INFORMATION OR SPECIFICATIONS		
				-1	1	BLANK	WHITE DELRIN/ACETAL		2	
				-3	1	STUD	NYLON	M6 X 1 X 38mm (MCMASTER-CARR #98882A600) MODIFIED	3	
			B/O	-5	4	FLAT WASHER	NYLON	M6 (MCMASTER-CARR #95610A570)	1	
			B/O	-7	4	HEX NUT	NYLON	M6 X 1 (MCMASTER-CARR #93800A600)	1	
			B/O	-9	A/R	ADHESIVE	CLEAR EPOXY	(GORILLA #4200102)	N/S	




This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS								
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED			







DART

TITLE

UNDOG CLUTCH BLANK

DWG NO.

RBFM632V6009124-3

REV 1

RBEN1032 V 0009 124-3								
MAT'L NYLC HEAT TREAT	N			UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES .XXX + .005 FRACTIONS ± 1/8				
FINISH				.XX ± .01 .X ± .1		25/		
SPEC				1. BREAK ALL SHARP EDGES .015 x 45° OR .015R 2. DIMENSIONAL LIMITS APPLY				
DRAWN BY:	CLOUGH	1						
CHECKED:	DUERFE	LDT	AFTER PLATING					
OPPS APPR:	ANDERS	SON	3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009					
QA APPR: LINDSAY					USED ON MODEL			
APPROVED: GILBERT				H175				
SCALE	DATE	6/1	13/2016	SHEET 3 OF	3			

(-3)

STUD